



DRIVE
SOLUTIONS

TwistLink and MetalLink **Link Belts**



**The spare tire
for your power transmission system.**

TwistLink V-Belts

Z - A - B - C

Description

TwistLink belts are designed to provide a practical alternative to conventional V-belts. Their interlocking link construction ensures excellent durability, reliability, and performance.


When properly tensioned, the interlocking link design significantly reduces belt elongation over time, helping maintain consistent drive performance and minimize maintenance requirements.

TwistLink V-belts can be manually adjusted to the required length within seconds and installed on the drive without dismantling components, simply by wrapping the belt around the system in the same way as a chain.

- **Material:** polyurethane
- **Operating temperature:** -40/+120 °C
- **Oil resistance:** excellent


Benefits

- Simplifies drive design through precise length adjustment
- Quick and easy installation and removal
- No re-tensioning required during service life



Sections and dimensional data

Section	a [mm]	b [mm]
Z	10	6
A	13	8
B	17	11
C	22	14



Section	Minimum pulley diameter [mm]
Z	45
A	80
B	125
C	229

Suitable for use with standard DIN 2211 V-belt pulleys.

Installation



Insert the tab at one end of the belt through two links simultaneously.



Flex the belt, rotate it, and pass the second tab through the end link.



Make sure the tab remains perpendicular to the belt running direction. Flip the belt over so that the tab side faces the pulley.

Disassembly

With the tabs facing upward, flex the belt and rotate the tabs 90° to easily disconnect the belt ends.

Applications

Compressors, industrial fans and blowers, food processing machinery, glass processing machines, mills, mixers and conveyor systems.

MetalLink V-Belts

Z - A - B - C

Description

MetalLink V-belts are specifically engineered for heavy-duty applications subject to high shock loads. They provide a high-performance replacement solution for conventional classical V-belts up to section C.

The modular link construction enables fast and reliable installation, even in locations with limited accessibility, allowing the belt to be fitted without dismantling drive components.

Thanks to their adjustable length design, **MetalLink** belts can be easily customized on site by adding or removing individual links. This significantly reduces the need to stock multiple belt lengths, simplifying inventory management and minimizing downtime.

- **Material:** polyurethane
- **Operating temperature:** -40/+120 °C
- **Oil resistance:** excellent


Benefits

- Simplifies drive design through precise length adjustment
- Quick and easy installation and removal
- No re-tensioning required during service life



Sections and dimensional data

Section	a [mm]	b [mm]
Z	10	6
A	13	8
B	17	11
C	22	14



Section	Minimum pulley diameter [mm]
Z	45
A	80
B	125
C	229

Suitable for use with standard DIN 2211 V-belt pulleys.

Installation



Pass the end pin through the two corresponding belt links simultaneously.

Rotate the belt and insert the adjacent pin into the remaining opening.

Using the supplied tool, rotate the pins by 90° until they are transverse to the belt running direction.

Make sure that the pins remain transverse to the direction of belt travel.

Disassembly

To release a belt link, rotate two adjacent pins by 90° using the supplied tool.

Applications

Compressors, industrial fans and blowers, food processing machinery, glass processing machines, mills, mixers and conveyor systems.



DRIVE
SOLUTIONS

SIT S.p.A.
Viale A. Volta, 2
20047 Cusago (MI) - Italy
Tel. +39.02.89144.1
Fax +39.02.89144.293
export@sitspa.it
www.sitspa.com

Factory
Via G. Carminati, 15
24012 Val Brembilla (BG) - Italy

AUTHORIZED DISTRIBUTOR

SIT GERMANY

SIT ANTRIEBSELEMENTE GmbH
Rieseler Feld 9 (Gewerbegebiet West)
D - 33034 Brakel
Tel. +49 52 72 39 28 0
Fax +49 52 72 39 28 90
E-mail: info@sit-antriebselemente.de
Web: www.sit-antriebselemente.de

SIT SWITZERLAND

SIT (Schweiz) AG
Lenzbühl 13
CH - 8370 Sirmach
Tel. +41 71 969 50 00
Fax +41 71 969 50 01
E-mail: info@sit-antriebstechnik.ch
Web: www.sit-antriebstechnik.ch

SIT SPAIN

DINAMICA DRIVE SOLUTIONS S.A.
Ctra. N-II, Km 592,6
E - 08740 S. Andreu De La Barca
(Barcelona)
Tel. +34 93 653 35 00
Fax +34 93 653 35 08
E-mail: dinamica@dinamica.net
Web: www.dinamica.net

SIT FRANCE

FOGEX SAS
215, Rue Henri Barbusse
F - 95100 Argenteuil
Tel. +33 1 34 34 46 00
Fax +33 1 34 34 46 01
E-mail: info@fogex.com
Web: www.fogex.com

SIT USA

SIT ELATECH, INC.
11540-A Cordage St
NC - 28273 Charlotte
Tel. +1 704 357 8811
Fax +1 704 357 8866
E-mail: info@sit-elatech.com
Web: www.sit-elatech.com

SIT CHINA

SIT ELATECH (SHANGHAI) LTD.
Room 804, Building 2, Alley 8666
Hunan Highway
Pudong New District
PRC - 201314 Shanghai
Tel. +86 021 51082206
Fax +86 021 64863511
E-mail: info@sit-shanghai.com
Web: www.sit-shanghai.com

SIT INDIA

SIT PTC INDIA PRIVATE LIMITED
S. No. 353/A, Gauddara Road,
A/p. Gauddara, Shriram Nagar,
Khed-Shivapur, Tal.: - Haveli,
Dist.: - Pune - 412205
Tel. +91 9158 5921 11
E-mail: a.nangre@sitspa.com
Web: www.sitspa.com